

QUILOSA PROFESSIONAL SINTESEL Miter Joint Sealant

Water-based sealant adhesive for sealing mitre joints and fine joints in metal, wood, PVC joinery. Easy to apply and to clean (only requiring water). Sintesel ingletes is a solvent-free, odourless product.

BENEFITS

- Good adhesion on aluminium (lacquered, anodizing), wood and PVC.
- Solvent free.
- Water resistant.
- Good UV resistance.
- No smell. Easily cleaned with water.
- Goes on white, dries translucent (1 hour in fine layer).

INTENDED USE

- Sealing of miter joints in aluminium carpentries (lacquered, anodizing), wood and PVC.

TECHNICAL DATA

Appearance	Value
Homogeneous dispersion	+
Uncured	Value
White	+
Solid Content [%]	50-53
Viscosity (Brookfield RVT, Sp 6/20 rpm) 23°C [mPa*s]	23000-27000
Application temperature [°C]	10-50
Cured	Value
Translucent	+

METHOD OF USE

Prior to application, read safety instruction presented in MSDS.

Surface preparation

- The surfaces to be glued must be tight, clean, dry and free of dust and grease.

Product preparation

- The product is ready to use.

Application

- To apply, using a brush or automatic mechanism, in the miter joint, a film of 1 to 2 mm of thickness.
- The dry product is completely translucent after approximately one hour, based on the temperature.

Works after completion of application

- Clean tools with water while the product is fresh. The cured material can be easily removed by mechanical means.

Remarks / restriction

- Do not apply the product when it is raining or there is a risk of immediate heavy rain.

REMARKS / RESTRICTION

Yield: aprox. 150 meters linear of joint by kg.

The information contained herein is offered in good faith based on Selena's research and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information shall not be used in substitution for customer's tests to ensure that Selena's products are fully satisfactory for your specific applications. Selena's sole warranty is that the product will meet its current sales specifications. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. Selena FM S.A. specifically disclaims any other expressed or implied warranty of fitness for a particular purpose or merchantability. Selena disclaims liability for any incidental or consequential damages. Suggestions of use shall not be taken as inducements to infringe any patent. Technical indications and data appearing in this brochure are based on our current knowledge and experience and we decline all responsibility for consequences derived from inadequate use. Therefore, our guarantee is limited exclusively to the quality of the product supplied. This technical information can be modified without notice. If necessary request it periodically.

TRANSPORT / STORAGE

Keep in a cool, dry place.

Store in its original closed package.

Protect from frosts.

Lifetime: 3 years.

CATALOGUE DATA

Nominal capacity / volume / size	Colour	Number of pieces per collective package	Catalogue Number	Index	EAN Code
500 gr	translucent	12	QSA-QACRUNI1-QP-16-gr-500-265	10044775	8411729083670

SAFETY AND HEALTH PRECAUTIONS

contains volatile monomers analogous to those present in water-based paints. For enclosed spaces it is, therefore, imperative that the room be aired. To avoid irritation, avoid all contact with eyes and skin while the sealant is wet. If contact occurs, wash affected areas with copious amounts of water and, if necessary, seek medical advice.

DO NOT WASH HANDS WITH SOLVENTS.

For more information request Safety Data Sheet.