



# CLOTH TAPE

62200 is a 70 mesh LDPE coated cloth tape with a natural rubber based adhesive. This universal tape can be torn by hand and is waterproof.

## Construction

<b>Adhesive</b>	Natural rubber resin blend
<b>Carrier</b>	Woven cotton / polyester cloth with polyethylene coating Black, silver

## Applications

Jointing and sealing.  
Masking, protecting and temporary repair applications.  
Packaging, holding and bundling.  
General maintenance.  
Interior and exterior use.

## Technical details

<b>Thickness</b>	0,30 mm
<b>Adhesive strength</b>	6,9 N/25 mm
<b>Tensile strength</b>	147 N/25 mm
<b>Temperature resistance</b>	+60°C
<b>Short term temperature</b>	+80°C
<b>UV resistance</b>	Limited
<b>Elongation</b>	12%
<b>Mesh</b>	70

## Recommendations for use

Temperature: between +5°C and +35°C. Surface must be clean and free from dust and grease. Avoid touching the tapes exposed adhesive surface in order to keep full adhesive performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24HRS at +23°C.

## Storage and shelf life

Clean and dry in a well ventilated area, preferably at a temperature between +10°C and +30°C. Stored under these conditions shelf life will be a minimum of 24 months.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Option Tape Specialties cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.



### OPTION TAPE SPECIALTIES

Frankrijkstraat 8  
9140 Temse - Belgium  
Tel. : +32 (0)3 710 19 19 - Fax : +32 (0)3 711 34 64  
info@optiontapespecialties.com - www.optiontapespecialties.com