

# TECHNICAL DATA SHEET GEKO BLIND

ITEM: COPREN SKIN FR120/0 THICKNESS mm10

Colour: ANTHRACITE

<b>COMPOSITION:</b>	100% PVC FORMULATO
<b>WEIGHT:</b>	1.200 g/m <sup>2</sup> +/-10%
<b>THICKNESS:</b>	10 mm +/-0,6 mm
<b>LENGTH:</b>	8m minimum.
<b>WIDTH:</b>	15mm +/- 0,6mm
<b>DENSITY:</b>	120 g/lt +/-10%
<b>THERMAL RESISTANCE:</b>	-20 / +65 °C

**Technical characteristics**

Tensile Strength	LONGITUDINAL TRANVERSE	kPa≥ 420 kPa≥ 380
Stretch at breaking point	LONGITUDINAL TRANVERSE	105% 108%
Resistance to cutting	LONGITUDINAL TRANVERSE	kg 3,7 kg 3,0
HARDNESS (SHORE)	00	32-34 +/- 15% at room temperature

Determination of resistance to compression calculated a 50% and 75% of relative deformation (UNI EN 826:13)			
RESISTANCE TO COMPRESSION			
Δ50		Δ75	
110 +/- 6 kPa	28 +/- 1,5 Kg	326 +/- 22 kPa	83,1 +/- 5,6 kg

Elastic thermoplastic material, it is recommended to store the product in a dry place protected from UV rays.

Material which by nature could have a certain level of stickiness and limited volatility of plasticizers, above all during the summer months.

The side exposed to the air (not the adhesive side) could appear wrinkled.

Coated in PVC created and produced in Italy.

Conforms with REACH regulations

Conforms with RoHS and does not contain Pb, Hg, Cd, CrVI, PBB, PBDE, Deca BDE in concentrations above 0,1%

The information contained in this technical data sheet are the results of internal tests. The end user must ensure that the product is suitable for their individual needs.