

## 1. General description

Professional cleaning of painted and bare metal surfaces contaminated with rust, lime, algae, oils and tar.



## 2. Features

- Takes rust and rust stains on painted or plastic surfaces away.
- Effective against a wide range of scales.
- Will quickly remove numerous different types of soiling and contamination.
- Safe to be used on most substrates. In case of doubt, test prior to application.
- Slightly foaming for better contact and economic product consumption.
- Prevents damage to the original surface due to excessive scratching.
- Non flammable.
- Composed of > 90% anorganic components and biodegradable organic components.
- Not classified as dangerous for the aquatic environment.

## 3. Applications

- All outdoor, painted steel constructions.
- Steel construction.
- Ship repair.
- Agricultural equipment.
- Oil rigs and related off shore equipment.



Manufactured by :  
**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele Belgium  
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)





#### 4. Directions

- Stir or mix bulk products well before use.
- Test before use on sensitive materials.
- Do not use on energized equipment.
- Do not mix with other products.
- Apply directly, in concentrated form.
- Work with a nylon brush in circular movements.
- Let react for 15 minutes.
- Rinse with cold water after application.
- Repeat if necessary.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

#### 5. Typical product data (without propellant)

Appearance	Not available.
Color	Colourless to yellow.
Odor	Characteristic odor.
Density	1.228 g/cm <sup>3</sup> (@ 20°C).
pH	< 2

#### 6. Packaging

Bulk	20 KG
	2x5 KG

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com) We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.


Version CRC\_GREEN-FERROKLEEN\_PRO-20120403

Date



Manufactured by :  
**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele Belgium  
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34  
[www.crcind.com](http://www.crcind.com)





Technical data sheet  
**FERROKLEEN PRO**

Reference : 30199 - 30089

---



Manufactured by :  
**CRC Industries Europe bvba**  
Touwslagerstraat 1  
9240 Zele Belgium  
Tél.: (32)(0) 52/45.60.11 Fax : (32)(0) 52/45.00.34  
**www.crcind.com**

3/1

