

QUICK WAX PLUS

Description:

Highly concentrated, high performance car wax; good quality/price ratio. It disaggregates the water layer quickly and makes the water drops slip away easily. In summertime it avoids the halo left by water drops on cars.

Directions for use:

Dilution:

Automatic: 10-30 ml / car

Pre-dilution:

Pre-dilution is not recommended.

Add pure.

The storage method and water quality can influence the shelf life of the solution.

Warnings:

When handling the product, observe the recommendations in the safety data sheet, the manufacturer's warnings for the devices and materials involved and, if necessary, test tolerability. Keep the container closed and use only caps with a passage for the tubing. Colour changes and cloudiness may occur due to the raw materials used, without this resulting in a decrease in performance and/or quality.

Warnings:

To handle the product, follow the precautionary advice on the safety data sheet.

Technical features:

Appearance and colour: yellow liquid

Odour: characteristic

pH: 4,7 ± 0,5

Flash point: > 60 °C

Relative density: 0,98 g/cm3 ± 0,05

Solubility in water: partially soluble

Solubility in oil: partially soluble

Storage:

In unopened packaging and stored away from direct sunlight and frost.

Packaging:

PACKAGING	BOX	ITEM CODE
JERRY-CAN 5 L	-	71525
JERRY-CAN 25 L	-	70558

Fra-Ber s.r.l.

The above data do not constitute specifications and are subject to normal production tolerances.

The data contained are the result of technological research in our laboratory and are provided purely for information purposes.

We exclude all liability deriving from an incorrect choice of product and lack of necessary precautions, which must always be verified by the user.

FRA-BER s.r.l.
T +39 0363 905287
F +39 0363 905290

SEDE LEGALE
REGISTERED OFFICE
 Via San Paolo n. 7
 20121, Milano (MI) Italy

SEDE OPERATIVA
OPERATING OFFICE
 Via M. Merisi 40-46
 24051, Antegnate (BG) Italy


www.fra-ber.it
 info@fra-ber.it
 C.F. / P.IVA 03351820166