



SAFETY DATA SHEET

Armor All® Cockpit Shine New Car (Odour Elimination)

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended).

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Armor All® Cockpit Shine New Car (Odour Elimination)
Product number 83500, 83300

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaning and restoring automotive interiors.
Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Energizer Trading Ltd
 Sword House
 Totteridge Road
 High Wycombe
 HP13 6DG
 UK
 Tel: +44 845 602 1995
 euregulatory@energizer.com

Αντιπρόσωποι & Διανομείς:

LEO. PATRIOTIS LTD.

Τ.Κώδικας 51533, 3506 Λεμεσός
 Τάσου Λειβαδίτη 2, 3118 Λεμεσός
 E-mail: info@patriotis.com
 Τηλ.: 77771100, Φαξ: 25872175
 Ώρες Εργασίας: 08:00-17:30

Τηλ. Κέντρου Δηλητηριάσεων: 1401

Ώρες Λειτουργίας: 24 ώρες/ημέρα & 7 ημέρες/εβδομάδα

Cyprus Poison Center: 1401

Working Hours: 24h/day & 7d/week

1.4. Emergency telephone number

Emergency telephone +44 1495 350234
 Monday - Thursday: 0830 - 1700
 Friday: 0830 - 1530

National emergency telephone number Product information has been submitted to the UK National Poisons Information Service (NPIS) and is accessible to medical health professionals.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)


Physical hazards Aerosol 1 - H222, H229
Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H336 Asp. Tox. 1 - H304
Environmental hazards Aquatic Chronic 3 - H412

Physicochemical Containers can burst violently or explode when heated, due to excessive pressure build-up. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

2.2. Label elements

Armor All® Cockpit Shine New Car (Odour Elimination)

Hazard pictograms



Signal word

Danger

Hazard statements

EUH208 Contains hydroxyisohexyl 3-cyclohexene carboxaldehyde. May produce an allergic reaction.
 H222 Extremely flammable aerosol.
 H229 Pressurised container: may burst if heated.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P271 Use only outdoors or in a well-ventilated area.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, propan-2-ol, White mineral oil (petroleum)

Detergent labelling

≥ 30% aliphatic hydrocarbons, < 5% perfumes, Contains HYDROXYISOHEXYL 3-CYCLOHEXENE CARBOXALDEHYDE

Supplementary precautionary statements

P261 Avoid breathing vapour/ spray.
 P264 Wash contaminated skin thoroughly after handling.
 P273 Avoid release to the environment.
 P280 Wear protective gloves, eye and face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P332+P313 If skin irritation occurs: Get medical advice/ attention.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313 If eye irritation persists: Get medical advice/ attention.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTRE/doctor if you feel unwell.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Armor All® Cockpit Shine New Car (Odour Elimination)

Hydrocarbons, C3-4-rich, petroleum distillate	50 - 100%
CAS number: 68512-91-4 EC number: 270-990-9	
Contains <0.1% w/w 1,3-butadiene (CAS: 106-99-0).	
Classification	
Flam. Gas 1A - H220	
Press. Gas (Liq.) - H280	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	10 - <25%
CAS number: — EC number: 927-510-4	
Classification	
Flam. Liq. 2 - H225	
Skin Irrit. 2 - H315	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	
propan-2-ol	10 - <25%
CAS number: 67-63-0 EC number: 200-661-7	
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
White mineral oil (petroleum)	10 - <25%
CAS number: 8042-47-5 EC number: 232-455-8	UK REACH registration number: UK-01-2029359895-7-XXXX
Classification	
Asp. Tox. 1 - H304	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
Ingestion	Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if any discomfort continues.

Armor All® Cockpit Shine New Car (Odour Elimination)

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Continue to rinse for at least 15 minutes. Get medical attention if symptoms are severe or persist after washing.

Eye contact Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if symptoms are severe or persist after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.

Ingestion Due to the physical nature of this product, exposure by this route is unlikely. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Skin contact Repeated exposure may cause skin dryness or cracking. Redness. Irritating to skin. May cause skin sensitisation or allergic reactions in sensitive individuals.

Eye contact May cause discomfort. Irritating to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically. Keep affected person under observation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up. Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. Vapours may form explosive mixtures with air.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Oxides of carbon. Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment for firefighters Use protective equipment appropriate for surrounding materials. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Evacuate area. No smoking, sparks, flames or other sources of ignition near spillage. Risk of explosion.

Armor All® Cockpit Shine New Car (Odour Elimination)

For non-emergency personnel No action shall be taken without appropriate training or involving any personal risk.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Eliminate all ignition sources if safe to do so. Do not touch or walk into spilled material. Ventilate closed spaces before entering them. Use only non-sparking tools. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections See Section 11 for additional information on health hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Provide adequate ventilation. Ground/bond container and receiving equipment. Keep away from heat, sparks and open flame.

Advice on general occupational hygiene Avoid contact with eyes and prolonged skin contact. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a cool and well-ventilated place. Keep away from heat, sparks and open flame. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Take precautionary measures against static discharges.

Storage class Flammable compressed gas storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Hydrocarbons, C3-4-rich, petroleum distillate

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

propan-2-ol

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

WEL = Workplace Exposure Limit.

propan-2-ol (CAS: 67-63-0)

Armor All® Cockpit Shine New Car (Odour Elimination)

DNEL

Workers - Inhalation; Long term systemic effects: 500 mg/m³
 Workers - Dermal; Long term systemic effects: 888 mg/kg/day
 General population - Inhalation; Long term systemic effects: 89 mg/m³
 General population - Dermal; Long term systemic effects: 319 mg/kg/day
 General population - Oral; Long term systemic effects: 26 mg/kg/day

PNEC

- Fresh water; 140.9 mg/l
- marine water; 140.9 mg/l
- STP; 2251 mg/l
- Sediment (Freshwater); 552 mg/kg
- Sediment (Marinewater); 552 mg/kg
- Soil; 28 mg/kg
- Oral; 160 mg/kg

tetramethyl acetyloctahydronaphthalenes (CAS: 54464-57-2)

DNEL

Workers - Inhalation; Long term systemic effects: 7.33 mg/m³
 Workers - Dermal; Long term systemic effects: 3.6 mg/kg/day
 Workers - Dermal; Long term local effects: 0.648 mg/cm²
 General population - Inhalation; Long term systemic effects: 2.16 mg/m³
 General population - Dermal; Long term systemic effects: 2.15 mg/kg/day
 General population - Dermal; Long term local effects: 0.380 mg/cm²
 General population - Oral; Long term systemic effects: 1.25 mg/kg/day

PNEC

Fresh water; 0.0028 mg/l
 marine water; 0.00028 mg/l
 STP; 10 mg/l
 Sediment (Freshwater); 3.73 mg/kg
 Sediment (Marinewater); 0.75 mg/kg
 Soil; 2.7 mg/kg
 Oral; 10 mg/kg

tetrahydro-2-isobutyl-4-methylpyran-4-ol, mixed isomers (cis and trans) (CAS: 63500-71-0)

DNEL

Workers - Inhalation; Long term systemic effects: 6.1 mg/m³
 Workers - Dermal; Long term systemic effects: 3.9 mg/kg/day
 General population - Inhalation; Long term systemic effects: 1.8 mg/m³
 General population - Dermal; Long term systemic effects: 2.4 mg/kg/day
 General population - Oral; Long term systemic effects: 1 mg/kg/day

PNEC

Fresh water; 0.094 mg/l
 marine water; 0.009 mg/l
 STP; 10 mg/l
 Sediment (Freshwater); 0.412 mg/kg
 Sediment (Marinewater); 0.041 mg/kg
 Soil; 0.09 mg/kg

benzyl acetate (CAS: 140-11-4)

DNEL

Workers - Inhalation; Long term systemic effects: 9 mg/m³
 Workers - Dermal; Long term systemic effects: 2.5 mg/kg/day
 General population - Inhalation; Long term systemic effects: 2.2 mg/m³
 General population - Dermal; Long term systemic effects: 1.3 mg/kg/day
 General population - Oral; Long term systemic effects: 1.3 mg/kg/day

Armor All® Cockpit Shine New Car (Odour Elimination)

PNEC Fresh water; 0.018 mg/l
 marine water; 0.002 mg/l
 STP; 8.55 mg/l
 Sediment (Freshwater); 0.526 mg/kg
 Sediment (Marinewater); 0.053 mg/kg
 Soil; 0.094 mg/kg

Menthyl acetate (CAS: 89-48-5)

DNEL Workers - Inhalation; Long term systemic effects: 33.6 mg/m³
 Workers - Dermal; Long term systemic effects: 9.5 mg/kg/day
 General population - Inhalation; Long term systemic effects: 8.3 mg/m³
 General population - Dermal; Long term systemic effects: 4.8 mg/kg/day
 General population - Oral; Long term systemic effects: 4.8 mg/kg/day

PNEC Fresh water; 0.0027 mg/l
 marine water; 0.00027 mg/l
 STP; 0.26 mg/l
 Sediment (Freshwater); 0.434 mg/kg
 Sediment (Marinewater); 0.043 mg/kg
 Soil; 0.085 mg/kg
 Oral; 317 mg/kg

hydroxyisohexyl 3-cyclohexene carboxaldehyde

DNEL Workers - Inhalation; Long term systemic effects: 3.67 mg/m³
 Workers - Dermal; Long term systemic effects: 1.45 mg/kg/day
 Workers - Dermal; Long term local effects: 2.5 mg/cm²
 General population - Inhalation; Long term systemic effects: 1.09 mg/m³
 General population - Dermal; Long term systemic effects: 0.87 mg/kg/day
 General population - Dermal; Long term local effects: 1.5 mg/cm²
 General population - Oral; Long term systemic effects: 0.63 mg/kg/day

PNEC Fresh water; 0.0118 mg/l
 marine water; 0.00118 mg/l
 STP; 0.2 mg/l
 Sediment (Freshwater); 0.195 mg/kg
 Sediment (Marinewater); 0.0195 mg/kg
 Soil; 0.0321 mg/kg

Reaction Mass of Cis-4-(isopropyl)cyclohexanemethanol and Trans-4-(isopropyl)cyclohexanemethanol (CAS: 5502-75-0)

DNEL Workers - Inhalation; Long term systemic effects: 6.63 mg/m³
 Workers - Dermal; Long term systemic effects: 1.88 mg/kg/day
 General population - Inhalation; Long term systemic effects: 1.63 mg/m³
 General population - Dermal; Long term systemic effects: 0.94 mg/kg/day
 General population - Oral; Long term systemic effects: 0.94 mg/kg/day

PNEC Fresh water; 0.0044 mg/l
 marine water; 0.00044 mg/l
 STP; 1.9 mg/l
 Sediment (Freshwater); 0.266 mg/kg
 Sediment (Marinewater); 0.0266 mg/kg
 Soil; 0.051 mg/kg
 Oral; 41.78 mg/kg

Armor All® Cockpit Shine New Car (Odour Elimination)

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. All handling should only take place in well-ventilated areas. Avoid inhalation of vapours and spray/mists. Use explosion-proof electrical, ventilating and lighting equipment.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

Do not smoke in work area. Wash promptly with soap and water if skin becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'UKCA'-marked.

Environmental exposure controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Colourless.
Odour	Hydrocarbons. Characteristic.
Odour threshold	Not determined.
pH	Not determined.
Melting point	Not relevant.
Initial boiling point and range	Not relevant.
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Vapour pressure	3300 - 5300 mbar @ 25°C
Vapour density	Not determined.

Armor All® Cockpit Shine New Car (Odour Elimination)

Relative density	Not determined.
Bulk density	600 - 700 kg/m ³
Partition coefficient	Not determined.
Auto-ignition temperature	Not relevant.
Decomposition Temperature	Not relevant.
Viscosity	Not determined.
Explosive properties	Not considered to be explosive.
Oxidising properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.

9.2. Other information

Volatile organic compound 95.80 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight. Avoid heat, flames and other sources of ignition. Avoid the accumulation of vapours in low or confined areas.
Pressurised container: may burst if heated

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Decomposition at ambient temperatures may generate the following substances: Carbon dioxide (CO₂). Carbon monoxide (CO). Acrid smoke or fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Armor All® Cockpit Shine New Car (Odour Elimination)

Skin corrosion/irritation

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Summary The product contains a small amount of sensitising substance. May cause skin sensitisation or allergic reactions in sensitive individuals.

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

Toxicological information on ingredients.

Hydrocarbons, C3-4-rich, petroleum distillate

Germ cell mutagenicity

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information.

Reproductive toxicity

Reproductive toxicity - fertility One-generation study - NOAEC 10000 ppm, Inhalation, Rat P REACH dossier information.

Reproductive toxicity - development Developmental toxicity: - NOAEC: 10426 ppm, Inhalation, Rat REACH dossier information.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,840.0

Species Rat

Notes (oral LD₅₀) REACH dossier information. Read-across data.

ATE oral (mg/kg) 5,840.0

Armor All® Cockpit Shine New Car (Odour Elimination)

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,800.0

Species Rat

Notes (dermal LD₅₀) REACH dossier information. Read-across data.

ATE dermal (mg/kg) 2,800.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 23.3

Species Rat

Notes (inhalation LC₅₀) REACH dossier information. Read-across data.

ATE inhalation (vapours mg/l) 23.3

Skin corrosion/irritation

Animal data Dose: 0.5 ml, 4 hours, Rabbit Primary dermal irritation index: 1.42 Read-across data. REACH dossier information. Skin Irrit. 2 - H315

Serious eye damage/irritation

Serious eye damage/irritation Dose: 0.2 ml, 7 days, Rabbit REACH dossier information. Based on available data the classification criteria are not met. Read-across data.

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier information. Read-across data. Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative. REACH dossier information. Read-across data.

Reproductive toxicity

Reproductive toxicity - fertility Two-generation study - NOAEL 10560 mg/m³, Inhalation, Rat F1 REACH dossier information. Based on available data the classification criteria are not met. Read-across data.

Reproductive toxicity - development Developmental toxicity: - NOAEC: 1200 ppm, Inhalation, Rat REACH dossier information. Read-across data. No evidence of reproductive toxicity in animal studies.

propan-2-ol

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,840.0

Species Rat

Notes (oral LD₅₀) REACH dossier information.

ATE oral (mg/kg) 5,840.0

Skin corrosion/irritation

Armor All® Cockpit Shine New Car (Odour Elimination)

Animal data Primary dermal irritation index: 0/4 Erythema/eschar score: Oedema score: REACH dossier information.

Serious eye damage/irritation

Serious eye damage/irritation Dose: 0.1 ml, 1 second, Rabbit REACH dossier information. Irritating.

Skin sensitisation

Skin sensitisation Buehler test - Guinea pig: Not sensitising. REACH dossier information.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative. REACH dossier information.

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information.

Carcinogenicity

Carcinogenicity NOEL 5000 ppm, Inhalation, Rat REACH dossier information.

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H336 May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEC 5000 ppm, Inhalation, Rat REACH dossier information.

White mineral oil (petroleum)

Acute toxicity - oral

Notes (oral LD₅₀) > 5000 mg/kg, Rat REACH dossier information. Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) > 2000 mg/kg, Rabbit REACH dossier information. Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Dose: 0.5 ml, 24 hours, Rabbit Erythema/eschar score: No erythema (0). Oedema score: No oedema (0). REACH dossier information. Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Dose: 0.1 ml, 20 - 30 seconds, Rabbit REACH dossier information. Not irritating.

Skin sensitisation

Skin sensitisation Buehler test - Guinea pig: Not sensitising. REACH dossier information. Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Bacterial reverse mutation test: Negative. REACH dossier information. Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity NOAEL ≥ 1200 mg/kg/day, Oral, Rat REACH dossier information. Based on available data the classification criteria are not met.

Reproductive toxicity

Armor All® Cockpit Shine New Car (Odour Elimination)

Reproductive toxicity - fertility Screening - NOAEL ≥ 1000 mg/kg/day, Dermal, Rat P, F1 REACH dossier information. Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Aspiration hazard if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Toxicity Harmful to aquatic life with long lasting effects.

Ecological information on ingredients.

Hydrocarbons, C3-4-rich, petroleum distillate

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 49.47 mg/l, Fish
REACH dossier information.
QSAR

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 96 hours: > 13.4 mg/l, Oncorhynchus mykiss (Rainbow trout)
REACH dossier information.

Acute toxicity - aquatic invertebrates EL₅₀, 48 hours: 3 mg/l, Daphnia magna
REACH dossier information.
Read-across data.

Acute toxicity - aquatic plants EL₅₀, 72 hours: 29 mg/l, Selenastrum capricornutum
REACH dossier information.
Read-across data.

Acute toxicity - microorganisms EL₅₀, 48 hours: 26.81 mg/l, Tetrahymena pyriformis
QSAR
REACH dossier information.

Chronic aquatic toxicity

NOEC 0.01 < NOEC ≤ 0.1

Chronic toxicity - fish early life stage NOELR, 28 days: 1.534 mg/l, Oncorhynchus mykiss (Rainbow trout)
QSAR
REACH dossier information.

Chronic toxicity - aquatic invertebrates NOELR, 21 days: 1 mg/l, Daphnia magna
REACH dossier information.
Read-across data.

propan-2-ol

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 10000 mg/l, Pimephales promelas (Fat-head Minnow)
REACH dossier information.

Acute toxicity - aquatic invertebrates LC₅₀, 24 hours: > 10000 mg/l, Daphnia magna
REACH dossier information.

Armor All® Cockpit Shine New Car (Odour Elimination)

White mineral oil (petroleum)

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 96 hours: > 100 mg/l, Oncorhynchus mykiss (Rainbow trout)
REACH dossier information.

Acute toxicity - aquatic invertebrates LL₅₀, 48 hours: > 100 mg/l, Daphnia magna
REACH dossier information.

12.2. Persistence and degradability

Persistence and degradability The surfactant(s) contained in this product complies(comply) with the biodegradability criteria as laid down in The Detergents Regulations (as amended).

Ecological information on ingredients.

Hydrocarbons, C3-4-rich, petroleum distillate

Phototransformation Water - DT₅₀ : 1906 days
REACH dossier information.
Calculation method.

Biodegradation Water - Degradation (100%): 385.5 hours
REACH dossier information.
The substance is readily biodegradable.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Biodegradation Water - Degradation (83%): 16 days
Water - Degradation (98%): 28 days
Read-across data.
REACH dossier information.
The substance is readily biodegradable.

propan-2-ol

Biodegradation Water - Degradation (53%): 5 days
REACH dossier information.

Biological oxygen demand 1.19 - 1.72 g O₂/g substance REACH dossier information.

Chemical oxygen demand 2.23 g O₂/g substance REACH dossier information.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

Hydrocarbons, C3-4-rich, petroleum distillate

Partition coefficient log Pow: 2.3058 REACH dossier information. QSAR

12.4. Mobility in soil

Mobility The product has poor water-solubility.

Ecological information on ingredients.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Armor All® Cockpit Shine New Car (Odour Elimination)

Surface tension 20.7 mN/m @ 25°C REACH dossier information.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations Do not puncture or incinerate, even when empty.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

Armor All® Cockpit Shine New Car (Odour Elimination)

14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].
The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended).
The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail. IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways. ATE: Acute Toxicity Estimate. DNEL: Derived No Effect Level. LC50: Lethal Concentration to 50 % of a test population. LD50: Lethal Dose to 50% of a test population (Median Lethal Dose). PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative. BCF: Bioconcentration Factor.
Classification procedures according to SI 2019 No. 720	Aerosol 1 - H222, H229: Expert judgement. Asp. Tox. 1 - H304: On basis of test data., Calculation method. Skin Irrit. 2 - H315, Eye Irrit. 2 - H319, STOT SE 3 - H336, Aquatic Chronic 3 - H412: Calculation method.
Revision comments	Revised formulation. Section 2: Hazards identification // 2.2. Label elements.
Revision date	01/04/2021
Revision	7
Supersedes date	19/03/2020
SDS number	553

Armor All® Cockpit Shine New Car (Odour Elimination)

Hazard statements in full	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH208 Contains hydroxyisohexyl 3-cyclohexene carboxaldehyde. May produce an allergic reaction.
----------------------------------	---

The information supplied here is accurate to the best knowledge and belief of Energizer Trading Ltd, it is however, not intended as a warranty or representation, and should not be construed as such, for which Energizer Trading Ltd assumes any legal responsibility. Any information or advice obtained from Energizer Trading Ltd other than by means of this publication, and whether relating to Energizer Trading Ltd's products or other materials is also given in good faith. It remains at all times the responsibility of the customer, and user, to ensure that the materials are suitable for the particular purpose intended. Materials not manufactured, or supplied, by Energizer Trading Ltd when used instead of, or in conjunction with materials supplied by Energizer Trading Ltd, it is the customer's responsibility to ensure that all technical, and other information related to such materials is obtained from the manufacturer or supplier. Energizer Trading Ltd accepts no liability for the data contained within this document, as the information herein may be applied under conditions beyond our control, and in situations with which we may be unfamiliar. The information contained within this document is furnished upon condition that the customer and user of this product makes his own determination of the suitability of the product for his particular purpose.