

# <mark>GLUE STICK SOLVENT FREE</mark>



## **PRODUCT DESCRIPTION**

The well-known glue stick "Made in Germany" with a unique screw cap that prevents the glue from drying out. The glue formula consists of 98 % natural ingredients (including water) and is solvent free. Glues strong, fast and durable, glides smoothly, is highly efficient and of course cold washable.

# FIELD OF APPLICATION

Suitable for glueing paper, cardboard, photos, Styrofoam® (expanded polystyrene), labels, textiles, etc.

# PROPERTIES

- · Glues fast, strong and durable
- · Highly efficient and cold washable
- Solvent free glue formula with 98 % natural ingredients (incl. water)
- · Screw cap prevents glue from drying out

#### PREPARATION

**Surface Requirements:** Materials to be glued must be clean, dry and free from dust and grease. One of both surfaces must be absorbent.

## APPLICATION

#### **Directions for use:**

UHU stic is applied with light pressure onto the materials to be glued. The parts are put together immediately after applying the glue.

**Stains/residue:** UHU stic can be easily washed out with cold water.

## **TECHNICAL SPECIFICATIONS**

| Acid free:                      | Yes             |
|---------------------------------|-----------------|
| Chemical base:                  | Modified starch |
| Colour:                         | White           |
| Colour after curing/drying:     | Transparent     |
| Consistency:                    | Wax-like mass   |
| Drying/Curing time<br>approx.*: | 45 seconds      |
| pH-value approx.:               | 10,5            |
| Solvent free:                   | Yes             |
| Washable:                       | Yes             |

\* Curing time may vary depending on a.o. surface, product quantity used, humidity level and ambient temperature.

## **PHYSIOLOGICAL PROPERTIES**

UHU stic is physiologically safe.

#### **PACK SIZES**

Glue stick: 8,2g, 21g, 40g

### **STORAGE CONDITIONS**

Store in a dry, cool and frost-free place.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.