

PRO 50% EVO12 OAT

➤ DESCRIPTION

Anti-freeze for direct application, formulated with ethylene glycol and a mixture of organic technology (Psi-OAT) corrosion-inhibitors, as well as anti-cavitation, anti-lime and anti-foam additives, designed to protect the various metals in latest generation internal combustion engine cooling circuits, including the aluminium and light alloys, thereby providing efficient protection for the engine, radiator, water pump and heavy cooling circuit.

It's not recommended mixing this product with other coolants since this can reduce quality.

➤ PHYSICAL AND CHEMICAL PROPERTIES

ASPECT	LIQUID
COLOUR	FLUORESCENT GREEN, PINK, YELLOW OR BLUE
ODOR	CHARACTERISTIC
pH at 20°C	7,5 - 9,5
DENSITY at 20°C	1,100 +/- 1.150 g/cm ³
SOLUBILITY IN WATER	100% SOLUBLE
FLASH POINT	NOT APPLICABLE
FREEZING POINT	-36°C +/- 1 °C
BOILING POINT	+145°C

➤ SPECIFICATIONS

UNE 26.361.88,
ASTM D3306/4985, VW TL 774L AFNOR R 15/601
SAE J 1034
CUNA NC 956-16
FVV HEFT R 443
JIS K 2234
BS 6580 (GB)
KSM 2142, EMPA
NATO S 759, E/L 1415C
DEUTZ
DEUTZ-FAHR
HUERLIMANN
LAMBORGHINI TRATTORI
MAN DIESEL & TURBO
VOLVO CAR TR-31854114-002

➤ USE

*Suitable for all vehicle types and makes.
Indicated for all types of cooling systems.*

➤ PRESENTATION

Available packaging 1L, 4L, 5L, 20L, 60L, 200L y 1000L.