

# HIGH PERFORMANCE SILICONE LUBRICANT



## PRODUCT OVERVIEW

**WD-40® Specialist® High Performance Silicone Lubricant is a non-staining, hard working formula which provides excellent lubrication, won't attract dirt, and protects against moisture. It stops parts from sticking and can be used on high pressure equipment. This product can be used on metal, plastic, wood and rubber.**

## FEATURES AND BENEFITS

- ⊕ Dual action Smart Straw® applicator for wide area and precision spray applications
- ⊕ Excellent lubrication on plastics, rubber, wood and metal
- ⊕ Formulated for improved high pressure performance
- ⊕ Waterproofs and protects against moisture
- ⊕ Prevents rust and corrosion
- ⊕ Eliminates sticking and binding
- ⊕ Non-staining
- ⊕ Temperature range: -35°C to +200°C

**NSF H2 Registered #145374**



NARROW SPRAY



WIDE SPRAY

## TYPICAL APPLICATIONS

Belts, bearings, linkages, doors & hinges, tools, guide rails, valves, locks and hoists.

## DIRECTIONS FOR USE

Shake can well. Apply by spraying directly on surface to be lubricated and protected.

## TECHNICAL DATA

PROPERTY	HIGH PERFORMANCE SILICONE LUBRICANT
Appearance	Clear yellow liquid
SG	0.79 - 0.80
Discharge rate	0.7 - 1.2 g/s
Temperature range	Effective performance at temperatures from -35°C to +200°C
Solubility	Not miscible with water
NSF category	H2
Flammability	Classed as extremely flammable under current legislation
Compatibility	Metal, plastic, rubber and wood
Lubrication ASTM D-4172	Scar depth 0.68 mm
Extreme pressure lubrication ASTM 3233	816 lb

## PACKAGING SPECIFICATIONS

PRODUCT NUMBER	UNIT SIZE	CASE SIZE
44377	400ml	400ml x 12

