

3-IN-ONE Multi-Purpose Oil Technical Data Sheet

Typical Physical Characteristics – USA

Color & Appearance: Clear amber liquid

Odor: Faint citronella odor Odor Threshold: Not established

pH: Not applicable

Melting/Freeze Point: Not established Specific Gravity at 15°C: 0.86 - 0.94 Boiling Point/Range: >550°F Vapor Density: Not determined

Relative Density: 0.866 - 0.923 @ 20°C

Solubilities: Insoluble in water

Flash Point: Greater than 305°F Tag Open Cup

Evaporation Rate: Not determined

Flammability (solid, gas): Not applicable

VOC: 0%

Partition Coefficient; n-octanol/water: Not determined

Autoignition Temperature: Not determined Decomposition Temperature: Not determined Viscosity: 112 SUS (23.31 cSt) @ 100°F

Pour Point: Not determined

Flammability Limit: Not determined Vapor Pressure: Not determined

Product Features

An essential household tool since 1894, 3-IN-ONE® Multi-Purpose Oil is a versatile formula that removes grime, lubricates moving parts, penetrates rust, and protects tools and equipment. Its easy-to-use drip spout allows for quick and precise application with no overspray or splatter, making this multi-purpose oil a go-to solution for professional tradesmen and do-it-yourselfers alike.

3-IN-ONE® Multi-Purpose Oil has a fill level indicator strip so it's easy to know when you're running low and comes in easy-squeeze bottles for versatility. Use this long-lasting multi-purpose oil on hinges, nuts and bolts, bicycles, wheels—nearly everything with moving parts. Available in a 3 oz and 8 oz size.

UPC#: 0 79567 10035 5 (3 oz.) UPC#: 0 79567 10038 6 (8 oz.)



3-IN-ONE Multi-Purpose Oil and the Environment

- 3-IN-ONE Multi-Purpose Oil Product does not contain Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent Chromium (Cr6), Polybrominated biphenyls (PBB), or Polybrominated diphenylether complying with the restricted substances listed in Article 4(1) of the RoHS Directive.
- 3-IN-ONE Multi-Purpose Oil Product contains no ingredients requiring California Prop 65 labeling such as benzene or toluene.
- 3-IN-ONE Multi-Purpose Oil Product complies with California VOC regulations.



Recycle where allowed

Fluid Properties

Working Temperature Range: -15°F to 300°F

Surface Cautions:

Always test surfaces first. Do not immerse rubber parts in product.

Surface Compatibility:

Safe on multiple surfaces including metal, plastic and rubber,

First Aid Measures

Ingestion (Swallowed): While aspiration is unlikely due to viscosity, DO NOT induce vomiting. Call physician, poison control center or the WD-40 Company Safety Hotline at 1-888-324-7596 immediately.

Contains petroleum distillates, Avoid frequent or prolonged contact with skin,

REGULATORY

U.S. Federal Regulations:

CERCLA 103 Reportable Quantity: This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA TITLE III:

Hazard Category For Section 311/312: Non-Hazardous

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313

Reporting requirements: None

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory.

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65): This product does not require a California Proposition 65 warning.

VOC Regulations: This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules.

