
Product name	:	MoTip Industrial Chain Grease
Article number	:	090205
Supplier / Producer	:	MOTIP DUPLI B.V. Wolframweg 2 NL-8471 XC WOLVEGA Telephone number +31 561 – 69 44 00 Telefax number +31 561 – 69 44 31

Product description

High quality spray to lubricate chain-driven transmissions, which are liable to heavy load.

Applications

Chains
Chain driven transmissions, liable to heavy load
Conveyors

Product characteristics

To be processed like oil, with the properties of grease
Outstanding mechanical and thermal stability
Good adhesion
Dilatant
Prevents wear and sticking
Resistant to weather influences
Resistant to weak acids and bases
Water-repellent
Directed jetspray



Physical and Chemical Characteristics

Contents	:	500 ml
Basis	:	Synthetic Oil
VOC-content	:	Approximately 39% w/w
Colour	:	Transparent
Scent	:	Characteristic
Relative density at 20°C	:	0,844 g/ml
Yield	:	2,0 g/sec
Vapour pressure at 20°C	:	3 to 4 bar
4 Ball EP-test (ASTM D 2596)	:	3430 N
Temperature resistant	:	-50°C tot +200°C
pH-value	:	Neutral

Usage

Before use, carefully read the directions on the packaging and act accordingly.

The aerosol should have room temperature.
Best processing temperature 5 to 30°C.
Before use, shake the aerosol.

Apply industrial chain grease in a thin layer.

During the initial flow phase, when the spray can really penetrate the treated chain, the spray has a foaming effect.

Optimum lubrication is obtained after evaporation of the solvent.