

MOTIP Effect Fluor

Technical Information



Decorative, fluorescent lacquer with excellent adhesion to treat surfaces, treated and untreated, of metal, stone, wood, glass and various types of plastic. For an optimum result, apply a base layer of MoTip Deco Effect white primer. MoTip Deco Effect Fluorescent Lacquer is available in 4 colours, red-orange, pink, yellow and green.

Ord.-no: 302301, 302302, 302303, 302304

Quality & properties

Excellent coverage
Fast drying
Fluorescent

Physical & chemical data

Base: Nitrocombi resin
Colourname:

- red-orange
- pink
- yellow
- green

Degree of gloss: mat GU

Efficiency: 400 ML – 1,25 - 1,75 m²

Dry to touch: 10 - 20 min

Dust dry:

- 5 - 10 min
- 5 min

Completely dry: 120 min

Overcoatable: 120 min

Surfaces: metal, concrete, stone, wood, glass and various types of plastic

Minimum Working Temperature: 15 °C

Maximum Working Temperature: 25 °C

Flash point: n.a.

Temperature Resistance: 110 °C

Content: 400 ML

How to use

The surface should be clean, dry and free of grease. Slightly sand the surface (grain 600).

The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.