



Technical Information

| | | | | | |
|----------------------------|---|----------------------------|---------------------------|---------------|---------------|
| Product name | : | MoTip Marking Spray | | | |
| | | For manual use | | | |
| Colour | : | Blue | Red | White | Yellow |
| Article number | : | 000028 | 000029 | 000030 | 000031 |
| Supplier / Producer | : | MOTIP DUPLI B.V. | | | |
| | | Wolfraamweg 2 | | | |
| | | NL-8471 XC WOLVEGA | | | |
| | | Telephone number | +31 561 – 69 44 00 | | |
| | | Telefax number | +31 561 – 69 44 31 | | |

Product description

High quality, fast-drying marking spray to mark stone, concrete, asphalt and metal.

Product characteristics

Very high coverage
Wear resistant
Resistant to petrol, chemicals and weather influences
Fast drying
For manual use

Physical and Chemical Characteristics

| | | |
|---------------|---|------------------------|
| Contents | : | 600 ml |
| Base | : | Acrylic resin |
| VOC-content | : | Approximately 70% w/w |
| Solid content | : | Approximately 30% w/w |
| Coverage | : | Approximately 60 metre |
| Hardened | : | After 16 hours |

Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre-treatment

The surface must be clean, dry and free of grease.

Treatment

The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample.

Apply the marking spray in the desired width.

After use, clean the valve (hold the can upright and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.