



# SEALANT STRIP

## SELF-ADHESIVE SEALING STRIP FOR A LONG-LASTING WATERPROOF SEAL



### PRODUCT DESCRIPTION

Self-adhesive sealant strip for permanent beautiful and waterproof joints.

### FIELD OF APPLICATION

Suitable for waterproof sealing of joints along baths, shower cubicles, sinks, (kitchen) countertops and for decorative sealing of joints along windowsills, window- & door frames and floor and wall partitions.

Not suitable for bitumen, polyethylene (PE), polypropylene (PP), PTFE and aquaria.

### PROPERTIES

- Easy to apply (no cartridge gun needed)
- Waterproof
- Self-adhesive
- Good adhesion
- Remains white
- Resistant to cleaning agents

### PREPARATION

**Working Conditions:** Only apply at temperatures between +5 °C and +40 °C.

**Preliminary Surface Treatment:** Remove old (silicone) sealant residue thoroughly. Treat uneven surfaces, such as deep tile joints, with a fine filler.

**Tools:** Scissors, cutter, cleaner cloth.

### APPLICATION

**Coverage:** Contents suitable for 3.35 m.

#### Directions for use:

Clean the surface thoroughly using a non-abrasive sanitary sponge and degrease surface with ammonia and let it dry thoroughly. Take out the strip and roll out the strip entirely in order to straighten the strip. Start in the corner and cut the sealant strip to the right size, taking an extra 1-2 cm into account. Fold the strip inwards along its entire length, remove and gently pull back the first part of the backing tape. Place the strip onto the joint and press the strip firmly downwards onto the joint. NOTE: Press the strip firmly to the surface and make sure the strip adheres at every spot, especially in the tile joints. Apply the other part of the strip(s) in the same way. In corners, cut bottom part of both strips diagonally (in 45° angle). Place both strips onto the joint corner. Press the strips again firmly towards each other and onto the surface.

**Advice:** For the best adhesion warm the surface gently.

Warming the Sealant Strip gently with a hair dryer or by placing it on a radiator will make the strip more flexible and easier to apply. After applying the sealant strip, warm it again and press it firmly onto the surface.

**Points of attention:** In case of a strong moving joints its recommended to use a silicone or polymer sealant. Do not stretch the strip or touch the adhesive layer with your fingers. Wait 24 hours before using the sanitary facilities. The strip can be cleaned with non-aggressive cleaning agents. The strip is NOT (over) paintable.

### TECHNICAL SPECIFICATIONS

Colour:	White
---------	-------

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.