



EVOX 15W40

DESCRIPTION

Excellent quality and long service life mixed multigrade lubricant. High performance oil for all types of diesel and gasoline passenger cars, turbocharged, etc.

- ❖ It helps to reduce the emission of exhaust gases and, due to its low phosphorus content, it lengthens the life of the catalysts
- ❖ Long-lasting lubricant
- ❖ Anti-wear and anticorrosive qualities, detergent, dispersant
- ❖ Keeps carbonaceous particles in suspension

PHYSICAL-CHEMICAL PROPERTIES

TIPE OF ANALYSIS	METHOD	RESULTATS
<i>Grade SAE</i>	-----	15W40
<i>Density (g/mL)</i>	ASTM D-1298	0.860-0.875
<i>Viscosity at 40°C, cst</i>	ASTM D-445	90-120
<i>Viscosity at 100°C, cst</i>	ASTM D-445	12,5-16,3
<i>TBN mgKOH/g</i>	ASTM D-2896	>7.0
<i>Viscosity index</i>	ASTM D-2270	140
<i>Freezing point min, °C</i>	ASTM D-97	-27°C
<i>Flash point min, °C</i>	ASTM D-92	>215°C
<i>Sulphated ash,% max, mass</i>	ASTM D-874	<1,5

USE

Supermultigrade lubricant indicated for light gasoline and diesel engines, passenger cars, trucks, buses and industrial equipment.

SPECIFICATIONS

API CF-4/SF
ACEA E2
MB 228.1
MAN 271

PRESENTATION

Available packaging 1L, 4L, 5L, 25L, 60L, 204L y 1000L