

MOTIP Vaseline Spray

Technical Information



Lubricate and protect parts such as screws, bolts and ultra-light materials with MOTIP Vaseline Spray. Vaseline Spray is water-repellent, pH-neutral and resistant to the weather and weak acids and bases. Vaseline Spray is a universal, transparent, lubricant and preservative with excellent adhesion.

Ord.-no: 290302, 090302

Quality & properties

- Water-repellent
- Excellent adhesion
- Prevents wear and sticking
- Resistant to weather influences, weak acids and bases
- Excellent corrosion prevention

Physical & chemical data

- Base: Vaseline
- Colourname: white
- Surfaces: Battery poles, Audio controls, Fasteners, Antennas, Electrical Connections, Protection for ultra light material (ultra light planes, wind turbines)
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content:
 - 200 ML
 - 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Apply vaseline spray in a thin layer.
- The optimum lubrication is obtained after evaporation of the solvent.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.