



Technical Information

Product name	:	MoTip Bitumen Based Undercoating, brush can
Article number	:	000016 00173
Contents	:	1.300 gram 2.500 gram
Supplier / Producer	:	MOTIP DUPLI B.V. Wolfraamweg 2 NL-8471 XC WOLVEGA
		Telephone number +31 561 – 69 44 00
		Telefax number +31 561 – 69 44 31

Product description

High quality preservative to treat the underside of vehicles.

Product characteristics

Remains flexible
Excellent adhesion
Resistant to weather influences
Resistant to weak acids and bases
Excellent corrosion prevention
Sound-absorbing

Physical and Chemical Characteristics

Colour	:	Black
VOC-content	:	Approximately 40% w/w
Coverage	:	2 to 3 m ² 4 to 6 m ²
Dust dry	:	After approximately 60 minutes

Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

Remove loose old lacquer and rust and sand the surface.

Treatment

The surface should be clean, dry and free of grease. The brush can should have room temperature. Best processing temperature 15 to 25°C.

Apply the undercoating in the required layer thickness.

After use, clean the tools used with white spirit.

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.