



SILICONE REMOVER

TO SAFELY AND THOROUGHLY REMOVE CURED SILICONE SEALANT RESIDUES



STORAGE CONDITIONS

At least 24 months after date of manufacture. Store in properly sealed packaging in a dry place at between +5°C and +25°C.

PRODUCT DESCRIPTION

For thoroughly removing cured silicone sealant residues Simple and safe to use without damage.

FIELD OF APPLICATION

Suitable for thoroughly removing cured silicone sealant residues in joints and on substrates. Can be used on ceramic tiles, glass, metal, synthetics, laminates, aluminium and enamels. Not suitable for to be used on nylon. May cause staining on porous materials and painted surfaces.

PROPERTIES

- Safe to use without damage
- Easy to apply
- Thorough effect

PREPARATION

Working conditions: Do not use in temperatures $\leq +5^{\circ}\text{C}$.

Surface requirements: The substrate must be properly dry, clean and free of dust and grease. Remove as much of the existing silicon sealant as possible .

Tools: Use a sharp knife/putty knife to cut away the silicone sealant as much as possible and a dry cloth for the last remaining bits.

TECHNICAL SPECIFICATIONS

Chemical base: Organic solvent thickened to a paste.

Colour: Brown

Viscosity: approx. 0 mPa.s., Thixotropic

Density: approx. 0.8 g/cm³