

PP Acrylic 28my LN X.T. AC 820LN TECHNICAL DATA SHEET

ALL ABOUT TAPES



DESCRIPTION:

High-grade water based low noise acrylic tape. Carrier BOPP 28my film, with 22my adhesive for manual carton sealing packaging applications.

Low noise properties. Available also in red, yellow, blue and green.

APPLICATIONS:

- Manual carton sealing.
- Adhesion on uneven surfaces due to high amount of adhesive.
- Particularly suitable for all sorts of packaging applications.
- Suitable for cold and hot temperatures.

PROPERTIES:

- Environmentally friendly and ecological adhesive.
- Moisture compatible after application.
- UV resistant adhesive.
- Resistance to temperature changes.
- Longevity of application

NOMINAL VALUES:

Backing Biaxially Oriented Polypropylene (BOPP)

Adhesive Acrylic (Water-based)

 Tensile Strength MD

 100 ± 20 (N/25mm)
 | ~ 23 (lb/in)

 TM 5004 by Afera

Elongation at Break MD

I40 ± 30 (%) TM 5004 by Afera

Peel Adhesion on Stainless Steel 5.8 ± I (N/25mm) | ~ 2I (oz/in) TM 500I by Afera

Shear to Steel Over 200 (h, 25mm x 25mm on stainless steel, 23°C) TM 5012 by Afera

Film thickness 28 ± I(mic) | ~ I,I0 (mils)

Film Colors	Transpar	ent 🛛		
Adhesive Color	Transpar	ent 🛛 🛛 🛛	Brown 📕	White 🗌
	Red 📕	Yellow 📃	Blue 📕	Green 📕

Effective: March 2022

Above nominal values are based on standard tests of AFERA, PSTC ASTM. Data should be considered indicative and subject to tolerances of raw materials.

The following data are nominal values to the structure of a structure of any structure of a