

WALLPAPER PASTE UNIVERSAL

WALLPAPER PASTE ON THE BASIS OF MODIFIED STARCH



PRODUCT DESCRIPTION

Wallpaper paste on the basis of modified starch.

FIELD OF APPLICATION

Suitable for applying all types of light, medium and heavy wallpaper, including paper, simplex, duplex and acrylic wallpaper.

PROPERTIES

- No clumping
- Non-staining
- Easy to apply
- Easily correctable
- Super-strong
- Ready for use within 10 minutes
- Airtight packaging
- Permanently fresh paste
- pH-neutral
- Moisture resistant

PREPARATION

Working conditions: Do not apply at temperatures below +10°C and/or relative humidity higher than 70%.

Personal safety: Physiologically safe.

Surface requirements: For an optimal result the surface must be porous, solid, clean, permanently dry, smooth, dust- and grease-free.

Preliminary surface treatment: Remove the old wallpaper using a wallpaper removal agent, then clean the surfaces in order to remove any remaining paste, grease or dust. Fill holes and cracks with wall filler to make the surface even and then coat any stains so that they do not show on the surface of the wallpaper. Prime highly absorbent surfaces first with diluted wallpapering

paste (20% water). Allow this primer layer to dry for at least 2 hours. Sand non-absorbent surfaces (e.g. latex layer) by initially opening up and then making the surface dust-free.

Tools: Pasting brush, bucket, stirring stick, wallpaper table. Clean tools immediately after use with water.

APPLICATION

Dilute: Dilute only with water

Mixture ratio: See table.

Coverage: See table.

| | Cold water | For | |
|-------------------------------|------------|-------|----------------|
| | | Rolls | m ² |
| Prepaste | 6 L | - | 50 |
| Light wallpaper | 5 L | 5 - 7 | 25 - 35 |
| Normal wallpaper | 4 L | 4 - 5 | 20 - 25 |
| Heavy wallpaper (vinyl, jute) | 3 L | 3 - 4 | 15 - 20 |

Directions for use:

Add the powder in small quantities to cold water while vigorously stirring until a lump-free paste is obtained. Let the paste rest and stir up vigorously again after 10 minutes. The paste is now ready to use. Coat the wallpaper strips thoroughly and evenly with a fur roller or brush, making sure the edges are properly covered. Fold the strips double and allow the paste to soak in following the instructions of the wallpaper manufacturer. Apply a strip of paper to the wall and brush it smooth using a plastic spatula or brush. Always smooth the wallpaper from the centre to the edges, and from top to bottom. Make sure that the seams are properly pressed against each other.

Stains/residue: Remove traces of paste immediately by dabbing with a clean, dry cloth. Dried paste on the surface of the wallpaper can be removed by dabbing with a clean, damp cloth.

Advice: Ready-made paste remains workable for several days when stored tightly sealed.

Points of attention: Always hang wallpaper in accordance with the manufacturer's instructions.

TECHNICAL PROPERTIES

Moisture resistance: Good

TECHNICAL SPECIFICATIONS

Chemical base: Starch

Colour: White (Transparent when dry)

Solid contents: approx. 100 %

STORAGE CONDITIONS

At least 24 months after date of manufacture. Limited shelf life after opening. Close container properly and store in a dry, cool and frost-free place.