

DOT-4 BRAKE FLUID

DESCRIPTION

Hydraulic fluid Base 100% synthetic, for filling brake circuits and automobile clutches, coaches, trucks, ect. DOT-4 quality level.

PHYSICAL AND CHEMICAL PROPERTIES

TYPE OF ANALYSIS	METHOD	RESULTS
<i>Appearance and smell</i>		<i>Bright and transparent fluid, odorless</i>
<i>Density</i>	<i>ASTM D-1122-84</i>	<i>1.030-1.070</i>
<i>Viscosity at -20°C, MM2/s</i>	<i>ASTM D-445</i>	<i>1800</i>
<i>Viscosity at 100°C, cst</i>	<i>ASTM D-445</i>	<i>1,5</i>
<i>Humid boiling point min, °C</i>	<i>UNE-26-376</i>	<i>>128°C</i>
<i>Boiling point min, °C</i>	<i>UNE-26-375</i>	<i>>230°C</i>
<i>PH</i>	<i>UNE 26-387</i>	<i>7,0-11,5</i>

PROPERTIES

- ❖ *High boiling point in dry and wet, essential for the correct operation of the braking system*
- ❖ *Good protection against corrosion and oxidation*
- ❖ *Good lubricating power*
- ❖ *Excellent viscosity in wide temperature range*

EXCEEDED SPECIFICATIONS

*UNE 26-109-88
SAE J-1704
ISO 4925
FMVSS N-116 DOT-4*

PRESENTATION

Packaging available 500ML, 1 L, 4 L, 5 L, 20 L cans, 50 L and 204 L drums and 1000 L tanks.