



Granville Smooth Metal Paint

250ml, 750ml & 2.5 Litre

Product Description

Granville Smooth Paint is an advanced, easy to use formulation - even on vertical surfaces - just apply like a conventional gloss paint. It gives an attractive and protective finish to all types of substrate. On ferrous substrates it provides a tough impermeable barrier to air and moisture which effectively seals out corrosion. Unlike currently available metal finish paints, it does not contain harmful solvents and has been designed to be slower drying making it easier and safer to use.

Product Benefits

- Technologically advanced White Spirit formulation
- Designed to protect, decorate and rejuvenate metal surfaces
- Use for example on metal drainpipes, gates, ornaments, bicycles, garden furniture, vehicle chassis and on all types of industrial machinery
- Simple one can treatment. No Undercoat, No Primer, No Rust
- No special thinner required - just use white spirit
- Easy to use - even on vertical surfaces - use like a conventional gloss paint

Product Usage

Brush: Use a suitable sized brush, apply paint evenly using multi-directional strokes. Apply paint thickly and evenly then level out to avoid runs and sags.

Roller: Use a natural fibre roller. Cover the area evenly. Some thinning may be required (up to 5%)

Spray: Thin with white spirit. Apply multiple coats allowing paint to dry between coats. Use a gun pressure of 30-40 psi. Thin, depending on equipment used, by between 10-15%.

Use white spirit or turpentine substitute for thinning product and cleaning equipment.

Directions for Use

On ferrous substrate it is recommended to wire brush and abrade to remove loose material and to provide a key. It is also recommended to wash the surface with detergent and water to remove any grease deposits. On heavily rusted and pitted surfaces, first applying two coats of Granville Heavy Duty Rust Cure will improve the performance of the paint.



* image for illustrative purposes only.

Colour	Size	Part.	Barcode
Black	250ml	9500	5020618095002
	750ml	9501	5020618095019
	2.5L	9502	5020618095026
Charcoal	250ml	9512	5020618095125
	750ml	9513	5020618095132
	2.5L	9514	5020618095149
Dark Brown	250ml	9508	5020618095088
	750ml	9509	5020618095095
	2.5L	9510	5020618095101
Blue	250ml	9504	5020618095040
	750ml	9505	5020618095057
	2.5L	9506	5020618095064
Red	250ml	9540	5020618095408
	750ml	9541	5020618095415
	2.5L	9542	5020618095422
Gold	250ml	9516	5020618095163
	750ml	9517	5020618095170
	2.5L	9518	5020618095187
Yellow	250ml	9532	5020618095323
	750ml	9533	5020618095330
	2.5L	9534	5020618095347
Silver	250ml	9524	5020618095248
	750ml	9525	5020618095255
	2.5L	9526	5020618095262
Pearl Grey	250ml	9520	5020618095200
	750ml	9521	5020618095217
	2.5L	9522	5020618095224
Ivory	250ml	9536	5020618095361
	750ml	9537	5020618095378
	2.5L	9538	5020618095385
White	250ml	9528	5020618095286
	750ml	9529	5020618095293
	2.5L	9530	5020618095309





Granville Smooth Metal Paint

250ml, 750ml & 2.5 Litre

Storage Instructions

Store sealed in a cool, dry place away from direct sunlight.

Shelf Life

2 years from date of manufacture.

Specification Information

Working temperature of cured product: -20°C to +100°C

Coverage:@100um DFT: 5-6 m²/ltr

Touch dry: 1.5 hours

Tack free: After 4 hours

Overcoating: After 12 hours

Salt spray: panels coated with Granville Metal Finish Paint will pass 1000 hours salt spray exposure to ASTM B117 when applied to the recommended film thickness of 100um.

Artificial weathering: After 600 hours exposure to ASTM G53-77 panels coated with Granville Metal Finish Paint will show minimal colour and gloss degradation.

Impact resistance: DIN55 669 Granville Metal Finish Paint, once cured, shows excellent impact resistance.

Appearance	Coloured thixotropic liquid
Odour	Characteristic - solvent
Specific Gravity	1.0 depending on colour
Solubility	Insoluble in water
Flammability	Flammable as a liquid
Flashpoint	37°C
VOC	VOC in g/l 2004/42/II1(i):600g/l(2007)/500g/l(2010). Product contains 400g/l

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

** The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*

