


www.atlas-tapes.gr info@atlas-tapes.gr

MASKING TAPE 6290

TECHNICAL DATA SHEET



DESCRIPTION:

Saturated semi crepe paper masking tape coated with specially devel- oped cross-linked solvent based natural rubber adhesive. Recommended and tested for 60 minutes 60°C oven use, and 80°C for 30 minutes. Suitable for all general masking applications.

APPLICATIONS:

- Guaranteed spray painting automotive oven use in 60°C for 60 minutes.
- · General masking
- · Domestic DIY and Industrial general painting
- Holding
- Sealing
- Fixing
- · Light duty packaging

PROPERTIES:

- 60°C oven use for 60 minutes.
- Suitable for both metallic and plastic automotive surfaces
- Residue free removal
- Excellent tape to tape adhesion
- Solvent and thinner resistant
- High initial tack
- Easy tear
- Excellent conformability
- Suitable for water and solvent based paints
- Easy curving
- Easy application on uneven surfaces

ALL ABOUT TAPES



NOMINAL VALUES:

Backing

Impregnated Crepe Paper

Adhesive

Solvent-based, Natural Rubber

Tensile Strength MD

 $85 \pm 20 \text{ (N/25mm)} \mid \sim 19 \text{ (lb/in)}$

TM 5004 by Afera

Elongation at Break MD

9 ± 2 (%)

TM 5004 by Afera

Peel Adhesion on Stainless Steel

 $4.5 \pm 1 (N/25mm)) | \sim 16 (oz/in)$

TM 5001 by Afera

Paper thickness

 $95 \pm 15 \text{ (mic)} \mid \sim 3,74 \text{ (mils)}$

Total thickness

 120 ± 20 (mic) | \sim 4,72 (mils)

Application Range

60°C for 60 minutes

Paper Colors White ☐ Sharp Yellow Yellow Brown 84

Adhesive Color Transparent

✓