

DIMABIKE 2T

DESCRIPTION

Synthetic lubricating oil specially formulated for air-cooled 2-stroke engines with a pro-oil-gasoline mixture lubrication system.

- ❖ *Complete and fast miscibility with gasoline*
- ❖ *Increased engine power*
- ❖ *Facilitates starting*
- ❖ *Eliminates spark plug pearling*
- ❖ *Its high detergent power suppresses carbonaceous residues, keeping the segments and ports clean*
- ❖ *Reduces smoke emission*
- ❖ *Save fuel*
- ❖ *Maximum anti-wear and anti - flu protection*

PHYSICAL AND CHEMICAL PROPERTIES

TYPE OF ANALYSIS	METHOD	RESULTS
SAE Grade		2T
Density at 15°C	ASTM D-1298	0,85-0,90
Viscosity at 40°C, cst	ASTM D-445	>55
Viscosity at 100°C, cst	ASTM D-445	8-12
Freezing point min, °C	ASTM D-97	-20°C
Flash point min, °C	ASTM D-92	>120°C
Viscosity index	ASTM D-2270	>85

EXCEEDED SPECIFICATIONS

API TC
JASO FC
ISO-L-EGC

USE

Recommended for mopeds, motorcycles, chainsaws, equipment equipped with 2-stroke engines, etc. Mix with the fuel in the proportions recommended by the vehicle manufacturer.



AUTOMOTIVE CHEMICAL FLUIDS

PRESENTATION

Available packaging 125 ML, 1 L, 5L, 25L, 60L, 204L y 1000L

PROQUISUR

PRO DIMASOIL arlo

Los valores de características típicas que figuran en el cuadro son valores medios dados a título indicativo y no constituyen una garantía.
Estos valores pueden ser modificados sin previo aviso.

PROQUISUR SL | P. I. La Salina, 26-27 | 14960 RUTE (Córdoba) SPAIN | Tel. (+34) 957 538 743 | www.proquisur.com