

## MOTIP Effect Clear Lacquer

## Technical Information



Fast drying clear lacquer for decoration purposes. To treat surfaces, treated and untreated, of wood, metal, aluminium, glass, stone, and various types of plastic. Clear lacquer has excellent adhesion, excellent filling properties and a lasting gloss. Clear lacquer is scratch free and shock proof and resistant to weather influences. Carat Clear Lacquer is corrosion preventive and UV-resistant and non-fading.

**Ord.-no:** 302203, 302204, 302205

### Quality & properties

- Fast drying
- Excellent filling property
- Lasting gloss
- Scratch free and shock proof
- Resistant to weather influences
- Corrosion preventive
- UV-resistant and non-fading
- Excellent adhesion

### Physical & chemical data

- Base: Acrylic resin
- Colourname: transparent
- Efficiency: 0.270 – 1,25 - 1,75 m<sup>2</sup>
- Dry to touch: 10 min
- Dust dry: 5 min
- Completely dry: 60 min
- Overcoatable: 60 min
- Surfaces: wood, metal, aluminium, glass, stone and various types of plastic
- Minimum Working Temperature: 15 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Temperature Resistance: 110 °C
- Content: 0.270

### How to use

The surface should be clean, dry and free of grease. Slightly sand the surface (grain 600). The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre. Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol. After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds). The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.