



# DUCT TAPE

General purpose duct tape with strong initial tack and good adhesive power. Conformable and excellent adhesion on PE and PP.

## Construction

<b>Adhesive</b>	Synthetic rubber
<b>Carrier</b>	Woven cotton /polyester cloth

## Applications

Interior and exterior use.

Suitable for adhesion on smooth and rough surfaces such as stainless steel, glass, wood and polyethylene.

Repairing, sealing, holding, protecting and bundling.

## Technical details

<b>Thickness</b>	0,17 mm
<b>Adhesive strength</b>	20 N/25 mm
<b>Tensile strength</b>	75 N/25 mm
<b>Service temperature range</b>	-10°C to +60°C
<b>Short term temperature</b>	+75°C

## Recommendations for use

Temperature: between +10°C and +35°C. Surface must be clean and free from dust and grease. Avoid touching exposed adhesive surface of the tape, as this impairs the performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24HRS at +23°C.

## Storage and shelf life

Clean and dry in a well ventilated area, preferably at a temperature between +10°C and +30°C. Stored under these conditions shelf life will be a minimum of 12 months.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Option Tape Specialties cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.



### OPTION TAPE SPECIALTIES

Frankrijkstraat 8

9140 Temse - Belgium

Tel. : +32 (0)3 710 19 19 - Fax : +32 (0)3 711 34 64

info@optiontapespecialties.com - www.optiontapespecialties.com

Last version 08/05/2020