



Technical Information

Product name	:	MoTip Primer			
Colour 500 ml	:	Black	Grey	Red	White
Article number	:	04052	04054	04055	04056
Colour 150 ml	:	Grey	White	Red	
Article number	:	00101	00102	00103	
Supplier / Producer	:	MOTIP DUPLI B.V.			
		Wolfraamweg 2			
		NL-8471 XC WOLVEGA			
		Telephone number		+31 561 – 69 44 00	
		Telefax number		+31 561 – 69 44 31	

Product description

High quality, fast drying primer to treat surfaces, treated and untreated, of wood, metal, aluminium, glass, stone and various types of plastic..

Suitable primer as pre treatment for re-spraying with all lacquer systems (alkyd resin, nitro cellulose, 1-K acrylic and 2-K acrylic lacquers).

Product characteristics

Fast drying
Excellent coverage and filling property
Corrosion preventive
Easy to sand, both wet and dry (from grain 400)
Re-sprayable with all lacquer systems

Physical and Chemical Characteristics

Contents	:	500 ml	150 ml
Base	:	Nitro-cellulose binder	
VOC-content	:	Approximately 85% w/w	
Solid content	:	Approximately 15% w/w	
Coverage	:	1,5 to 2 m ²	Approximately 0,5 m ²
Dust dry	:	After 5 to 10 minutes	
Tack free	:	After 10 to 20 minutes	
Hardened/re-sprayable	:	After 2 hours	
Heat resistant	:	To 110°C	

Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

Treatment

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the primer in several thin layers. Before applying the next layer, again shake the aerosol.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.