

MOTIP Stone Chip Spray 500 ml (Medium Solid)

Technical Information



Protect the bottom and visible bodywork parts of your car against chips with MOTIP Stone Chip Spray. Stone Chip Spray can be resprayed with all paints and has an excellent rust prevention. Stone Chip Spray is resistant to the weather and weak acids and bases, is sound absorbing and remains flexible.

Ord.-no: 000001, 000005, 000006

Quality & properties

- Re-sprayable with all lacquer systems
- Remains flexible
- Very good adhesion
- Excellent corrosion prevention
- Resistant to weather influences
- Resistant to weak acids and bases
- Sound-absorbing

Physical & chemical data

Base: Synthetic resin
Colourname:

- black
- white
- grey

Dry to touch: 60 min
Dust dry: 30 min
Completely dry: 60 min
Overcoatable: 120 min
Surfaces: Underside and visible parts of the vehicles
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point: n.a.
Storage stability: 10 y
Content: 500 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly
Remove loose old lacquer and rust and sand the surface.
The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C.
Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.
Apply the Stone Chip Spray in several layers. After drying, without sanding, re-sprayable with all lacquer systems.
After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.