



LITEPLAST Crack Filler

DATA SHEET
01/2020



DESCRIPTION:

Lightweight filler ready to use, easy to apply, suitable for indoor and outdoor applications.

APPLICATIONS:

LITEPLAST is a light filler ready to use, recommended to repair and fill cracks, holes, fissures, etc, in wood surrounds, plasters or cement and in general, any kind of porous construction materials. It can be textured to resemble the characteristics of the surface to be filled.

PROPERTIES:

LITEPLAST dries very fast and does not shrink, nor crack. It can be sanded and painted once dried. Due to its high moisture resistance, it can be used outdoor.

INSTRUCTIONS:

Prepare the surface avoiding dust and removing any particle. Wet slightly the surface to be filled.

Apply LITEPLAST with a flexible spatula or directly from the tube. Trowel and smooth the surface to the desired shape and use water on the spatula to obtain a good smooth finish.

Once the product is dry it can be sanded and painted if necessary. At least let dry the product one hour before paint.

If the product becomes too dry, add some water to the putty and mix to proper consistency.

TECHNICAL FEATURES

Appearance:	White paste.
Viscosity:	Paste of thixotropic consistency.
Density tubes:	(23°C) 0,54 ± 0,02 g/cm ³
Density pot:	(23°C) 0,42 ± 0,02 g/cm ³
Base:	Water
Curing rate:	3-5 mm/24 h (23°C, 65% hr)

STORAGE:

At least 24 months in its closed original containers at a recommended temperature between 5 to 30°C.

CLEANING:

Cleaning can be done with water while the product is still fresh.

PRESENTATION:

Tube	50 ml and 150 ml
Pot	250 ml and 750 ml.
Cube	5 l.

HEALTH & SAFETY:

According to current legislation, LITEPLAST is safe and does not require any indication of specific safety, handling or storage.

For more information request the Safety Data Sheet.

"The information contained herein is offered in good faith based on Selena's research and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information shall not be used in substitution for customer's tests to ensure that Selena's products are fully satisfactory for your specific applications. Selena's sole warranty is that the product will meet its current sales specifications. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. Selena FM S.A. specifically disclaims any other expressed or implied warranty of fitness for a particular purpose or merchantability. Selena disclaims liability for any incidental or consequential damages. Suggestions of use shall not be taken as inducements to infringe any patent. Technical indications and data appearing in this brochure are based on our current knowledge and experience and we decline all responsibility for consequences derived from inadequate use. Therefore, our guarantee is limited exclusively to the quality of the product supplied. This technical information can be modified without notice. If necessary request it periodically."



Quilosa - Selena Iberia S.L.U.

Centro empresarial Rivas Futura, C/ Marie Curie 19, Planta 6.1, 28521 Rivas, Madrid, Spain,
Tel: +34 902 02 18 02 – Fax: +34 914 999 796, info@quilosa.es, www.quilosa.com