

# AIR MAX® MILDEW REMOVER

DESTROYS MOULD, ALGAE AND MOSS IN HUMID PLACES INDOORS OR OUTDOORS. CHILD-PROOF SAFETY CAP.



products; this could release dangerous gases (chlorine). Do not reuse bottle. Important: cover plants and metals. Prevent spattering on clothing (bleach stains), glossy paints (matting) and vertical blinds (discoloration). In case of contact, immediately rinse with water. Proper ventilation during use is necessary. Light coloured joints and vulnerable tiles may show a brown discoloration. Tip: test product in advance in an inconspicuous spot. Use on sprayed ceilings (spack) and walls is not advised. Brown discoloration can be undone with a sodium thiosulphate solution. More information at [info@bison.nl](mailto:info@bison.nl).

## TECHNICAL SPECIFICATIONS

**Base:** Sodium hypochlorite 50 g/l, active chlorine percentage approx. 5%

**Colour:** Light yellow

**Density:** approx. 1,09 g/cm<sup>3</sup>

**pH-value:** approx. 13

## SHELF LIFE

At least 12 months after date of manufacture. Store well-closed, upright, in a stable, dry, cool and frost-free place.

## PRODUCT DESCRIPTION

Destroys mould, algae and moss in humid places indoors or outdoors. Child-proof safety cap.

## FIELD OF APPLICATION

For walls, floors and joints in sanitary rooms, kitchens, basements, and garages. Also for outdoor use: façades, balconies and flowerpots.

## PROPERTIES

- Destroys mould, algae and moss
- With child-proof safety cap

## PREPARATION

**Working conditions:** Do not use at temperatures below +5°C.

**Preliminary treatment:** Do not remove mould or algae in advance. Cut away moss layers.

## APPLICATION

**Coverage:** For 4-6 m<sup>2</sup> (walls) or 12-16 m (joints).

### Directions for use:

Prepare childproof vaporizer for use by pressing tabs and twisting cap a quarter turn. Prevent spattering: always prepare bottle for use before spraying. Spray surface at a distance of 3-5 cm and allow to penetrate for approx. 10 minutes. In case of severe pollution, repeat treatment after 10 minutes. Thoroughly clean treated surface with a sponge and water. In case of elastic joints (e.g. silicone sealant), repeat entire process (spray and clean). After use, close vaporizer by twisting cap back a quarter turn. Once opened, store Mildew Remover® bottle in a safe place where it can do no harm.

**Stains/residue:** Bleach stains cannot be removed.

**Points of attention:** Attention! Do not use in combination with other

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.