



Technical Information

Product name	:	MoTip Tuning Line Engine Paint				
Colour	:	Red	Black	Aluminium	Blue	Green
Article number	:	04091	04092	04093	04094	04095
Supplier / Producer	:	MOTIP DUPLI B.V.				
		Wolframweg 2				
		NL-8471 XC WOLVEGA				
		Telephone number		+31 561 – 69 44 00		
		Telefax number		+31 561 – 69 44 31		

Product description

High quality lacquer to treat engine blocks.

Product characteristics

Good filling property
Lasting gloss
Scratch free and shock proof
Resistant to petrol, chemicals and weather influences
Corrosion preventive
Reduces the adhesion of dirt
Non-fading (UV-resistant)
Good adhesion
Elastic, resistant to temperature fluctuations

Physical and Chemical Characteristics

Contents	:	400 ml
Base	:	Alkyd resin
Colour	:	Red
VOC-content	:	Approximately 79% w/w
Solid content	:	Approximately 21% w/w
Gloss	:	High gloss 90 at an angle of 60°
Coverage	:	1,25 to 1,75 m ²
Dust dry	:	After 30 to 60 minutes
Tack free	:	After 3 hours
Hardened/re-sprayable	:	After 24 hours
Heat resistant	:	To 110°C
Peak	:	To 150°C

Usage

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment

De surface should be clean, dry and free of grease.

Treatment

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the lacquer in several thin layers. (Before applying the next layer, again shake the aerosol).

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.