

## MOTIP Copper Spray

Ord.-no.: 090301

### Technical Information



Prevent wear and sticking of screwed connections exposed to very high temperatures with MOTIP Copper Grease. Copper Grease has high thermal stability and is corrosion preventive. MOTIP Copper Grease is resistant to temperatures of - 40°C up to + 1.100°C.

#### Quality & properties

- Simplifies the future removal
- High thermal stability
- Resistant to chemicals and weather influences
- Prevents wear and sticking
- Corrosion preventive
- Excellent adhesion
- Directed jetspray

#### Physical & chemical data

- Base: EP-2 Grease with copper
- Colourname: Copper
- Smell: characteristic
- Surfaces: Brake parts, Exhaust parts, Screwed connections (which are exposed to high temperature), Battery Poles, Thread of Spark Plugs
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Spray rate: 1,26
- Vapour pressure: 3500/20 bar
- Flash point: n.a. °C
- Relative density: 0.767 g/ml
- Storage stability: 10 years
- Content: 500 ML

#### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Apply copper spray. The specific lubrication property is achieved after evaporation of the solvent (approximately 1 minute).

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

**As of November 24, 2021** – This release replaces all eventually earlier issued versions.