# DUPLI-COLOR UNIVERSAL PRIMER

## Technical Information




This Primer for universal use grants the excellent adhesion of the subsequent top coating with DUPLI-COLOR synthetic, nitro-combi or acrylic spray paints.
Suitable for the most surfaces, such as ceramics, eternite, carton, of course even on wood and metal.

**Ord.-no:** 325021, 328046, 467486, 319648, 319648-DF, 325021-AT, 325021-DG, 325021-DW, 328046-DG, 467486-AT, 467486-DG, 467486-DW

### Quality & properties

High-grade nitro-combi quality
Especially high filling power
Very good flow, smooth surface
Quick-drying
Protects from corrosion
Promotes best adhesion of the top coat on the subsoil
Optimizes the gloss of the top coat
Grants the economical application of the top coat
For indoor and outdoor applications

### Physical & chemical data

Base: Nitrocombi resin
Colourname:
- grey
- red
- beige

Smell: Characteristic
Degree of gloss: mat, 10 ±2
Efficiency: 400 ML – 0.8 m²
Dust dry: 15 min
Dry to touch: 30 min
Overcoatable: 2 - 4 h
Surfaces:
- Ceramics, eternite, carton, wood and metal.
- Ceramics, eternite, carton, wood and metal

Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point: n.a.
Storage stability: 10 years
Content:
- 400 ML
- 150 ML

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com

**How to use**

De-rust, sand and clean the surfaces to be painted.
Apply putty, if necessary.
The surface has to be clean, dry and free from rust and fat.
Shake cans for 2 minutes.
Test colour of spray and compatibility at an invisibible spot.
Egalize little dents and porous repair spots by repeated spraying of thin layers and sanding.
Spray from a distance of approx. 25 cm.
After drying (approx. 2-4 hours), wet-sand with sandpaper (grain 600), clean the surface and let it dry.
Afterwards apply the top coat.
Coatable with synthetic, nitro-combi or acrylic lacquers.
Do not spray over synthetic lacquers!

**Environmentally sound**

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal**

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

**Marking/Labelling**

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of August 4, 2025** – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com