SEALANT STRIP SANITARY SELF-ADHESIVE SEALANT STRIP





Check if sealant strip adheres well everywhere - especially in tile joints. Apply other strip(s) in same way. Make sure strips overlap in corners. Starting from corner, cut off overlapping pieces diagonally (45°) and press firmly again. **Stains/residue:** Remove tape residue with white spirit.

CURE TIMES

Dry/Cure time: approx. Wait for 24 hours before using sanitary installations. Before use, check if strip adheres well everywhere.

* Curing time may vary depending on a.o. surface, product quantity used, humidity level and ambient temperature.

TECHNICAL PROPERTIES

Water resistance: Very good

Chemicals resistance: Resistant to the usual cleaning products.

Paintability: Not paintable

TECHNICAL SPECIFICATIONS

Chemical base: Polyethylene (PE) with butyl rubber glue layer.

Colour: White

STORAGE CONDITIONS

24 months

PRODUCT DESCRIPTION

Self-adhesive sealant strip for permanently neat, waterproof joints along bath tub, shower tub, worktop and floor. Easy to apply.

FIELD OF APPLICATION

For neat, waterproof, decorative sealing of joints along bath tub, shower tub, washbasin, worktop, sink and floor.

PROPERTIES

- · Immediate adherence
- · Easy to apply
- ·Waterproof
- $\cdot \, \text{Decorative} \,$
- $\cdot \, \text{Permanently neat} \,$
- · Resistant to cleaning products

PREPARATION

Working conditions: From $+10^{\circ}$ C tol $+35^{\circ}$ C.

Preliminary surface treatment: Clean surface thoroughly with an abrasive and carefully remove any old sealant residue. Treat irregularities in surface, like deep tile joints, with a fine filler. Carefully degrease surface with methylated spirits or ammonia (not with white spirit!). Let dry well.

Tools: Scissors, knife.

APPLICATION

Directions for use:

Cut strip to size and leave a margin of approx. 10–15 mm. Start with the longest joint. Fold strip lengthwise and pull loose a corner of protective foil. Put one end of sealant strip on joint and apply while firmly pressing downward. Attention: do not stretch sealant strip while pressing! Cut off excess strip at end of joint.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.