



KRAFFT S.L.
P.O.Box 14
E-20140 Andoain - SPAIN
Fax: +34 943 410 430
Phone: +34 943 410 460
E-mail: export@krafft.es
Web site: www.krafft.es

TECHNICAL INFORMATION

B3672--I
11.03.2008
-1-

GRAPHITE LUBE

Penetrant oil, loos all

1- DESCRIPTION

Product based on solvents, lubricant oils, solid lubricants (graphite) and additives with low surface tension and high penetrating power.

2- APPLICATION

Very active lubricating and penetrating product for loosening, sliding or unscrewing of nuts, bolts, screws or any other metal part seized by rust build up, time effect or exposure to dirt.
Applied during assembly, prevents oxide build-up and ensures further disassembly.

3- CHARACTERISTICS

CHARACTERISTICS	METHODS	SPECIFICATIONS		
		MIN.	TYP.	MAX.
Appearance			Oily liquid	
Colour			Black	
Density at 20°C (g/cm ³)	UNE 5116-82	0.80		0.85
Dry Extract at 100°C (%)	K 30095-1		70	
Flash point (°C)	UNE 51024-87	55		
Viscosity at 40°C (cSt)	UNE 26382-88		3.5	
Freezing Point (°C)	UNE 51106-80		-37	

4- SPRAY CHARACTERISTICS

CHARACTERISTICS	METHODS	SPECIFICATIONS		
		MIN.	TYP.	MAX.
Propellant	E 00031		LPG	
Pressure at 5°C (bar)	E 00030	3.5		4.5
Discharge (g/s)	E 00047		1.5	

4- DIRECTIONS FOR USE

Pulverize on the part to be treated and let actuate 2 to 3 minutes

The information herein is offered in good faith based on KRAFFT's research and it is believed to be accurate. KRAFFT keeps the right to modify the specification without previous notice.