

---

|                            |   |   |
|----------------------------|---|---|
| <b>Product name</b>        | : | <b>MoTip Airco Cleaner</b>  |
| <b>Article number</b>      | : | <b>090508</b>   |
| <b>Supplier / Producer</b> | : | <b>MOTIP DUPLI B.V.</b><br><b>Wolframweg 2</b><br><b>NL-8471 XC WOLVEGA</b><br><b>Telephone number</b> <b>+31 561 – 69 44 00</b><br><b>Telefax number</b> <b>+31 561 – 69 44 31</b> |

---

### Product description

High quality cleansing foam to condition the air-conditioning in motor vehicles.

### Application

Air Conditioning

### Product characteristics

Effective cleaning foam  
Subtle scent  
Optimizes the functioning of the air-conditioning  
Prevents malfunction

### Physical and Chemical Characteristics

|                          |   |                       |
|--------------------------|---|-----------------------|
| Contents                 | : | 500 ml                |
| Basis                    | : | Tenside solution      |
| VOC-content              | : | Approximately 27% w/w |
| Appearance               | : | White foam            |
| Scent                    | : | Mint - Menthol        |
| Relative density at 20°C | : | 0,967 g/ml            |
| Coverage                 | : | One (1) treatment     |
| pH-value                 | : | 10 - 11               |



### Usage

**Before use, carefully read the directions on the packaging and act accordingly.**

The aerosol should have room temperature.  
Best processing temperature 5 to 30°C.  
Before use, shake the aerosol.

Before treatment, switch off the engine and the electrical installations.

Apply the foam to the condenser of the air conditioning by means of the enclosed adapter.  
Insert the adapter about 30 centimetres into the air inlet of the air conditioning and completely empty the can.

The location of the air inlet differs per brand, consult your dealer.

After applying, do not switch on the engine or the electrical installations for at least half an hour.  
In this half hour the foam will break and leave the system through the condensed water outlet as a fluid.