

MOTIP Paint Remover



Quality & properties

Spray pattern approximately 8 centimetre wide Gel structure Very effective User-friendly Also suitable for various specialty paints, such as camouflage paints and hammerfinish paints.

Technical Information

Remove old layers of paint from surfaces of stone, concrete, asphalt, metal and wood with MOTIP Paint Remover. Paint Remover has a gel structure and is userfriendly.

Ord.-no: 090410

Physical & chemical data

Base: Methylal Colourname: no colour Surfaces: Paintwork, Stonework, Pavement Minimum Working Temperature: 10 °C Maximum Working Temperature: 25 °C Flash point: n.a. Storage stability: 10 y Content: 500 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.

The aerosol should have room temperature.

Best processing temperature 10 to 25°C.

Before use, shake the aerosol and test the compatibility of the surface.

Apply paint remover generously and allow to take effect. The time to take effect depends on the quality and age of the lacquer to be removed.

Then, remove with a tool appropriate for this purpose. When required, repeat the treatment.

Contaminated paint remover should be regarded as chemical waste.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.