

### Technical datasheet

# PU Remover

# **Product description**

PU Remover is a ready to use gel for the easy removal of all remains of cured PU foam. The product is only suitable for non-porous surfaces.

# **Properties**

- Very active
- Odorless
- Free of aromatic hydrocarbons
- Biodegradable
- Easy to apply

#### **Applications**

Removal of all cured PU foam residues on non-porous surfaces.

# Technical data

Base	Water soluble solvents
Consistency	Gel
Density	ca. 1,54 ± 0,05 g/cm³
Solubility in water	Soluble

Footnote: Skinning time and curing speed may vary depending on environmental factors such as temperature, moisture, and type of substrates.

#### **Substrates**

Substrate types

Substrates: All non-porous substrates. We recommend a preliminary compatibility test on every surface.

Not suitable substrates

Do not use on untreated copper, brass, zinc, acrylic paint or PMMA (Plexiglass). Risk of staining on porous surfaces, plastics and lacquer or paint layers.

## **Application method**

Application method

Remove mechanically or cut away carefully as much cured foam as possible. Apply PU Remover by means of the enclosed brush onto the cured PU foam. Leave PU Remover for at least 30 minutes and maximum 2 hours. Remove dissolved foam with the enclosed spatula and wipe off with a dry cloth. If necessary, repeat the treatment by reapplying PU Remover. Prior to using the product, test whether surfaces are affected or not. Especially plastics and lacquer or paint layers can be sensitive to this.

- Ambient temperature
  - +5 °C to +35 °C
- Cleaning method damp cloth





# PU Remover

### **Health- and Safety Recommendations**

Take the usual labour hygiene into account. Consult the packaging label and safety data sheet for more information.

Always wear gloves and goggles.

Use only in well-ventilated areas.

In case of contact with skin, wash with water and soap.

#### Packaging/Logistics

Colour: Beige Packaging: 100 ml

Shelf life: 36 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C

#### Remarks

Always stick to recommended working time to avoid damage of the surface.

PU Remover may cause staining on porous surfaces (such as natural stone).

This technical data sheet replaces al previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.